



Model 110 Quick Closing Barrel Faucet

SPECIFICATION SHEET

Application

Designed for use on barrels, drums, and small utility tanks for low pressure or gravity flow dispensing. The normally-closed valve must be held in the open position for dispensing.

Features and Details

- Self closing
- Lockable
- Rated to 50 PSI
- **110**...Non-threaded outlet models include built-in hook makes it easy to dispense into small containers

Materials of Construction

- Body... Brass
- Cap... Brass
- Disc... Buna-N (FKM and PTFE available for non-threaded models only)
- Spring... Stainless steel

Certifications and Listings

¾" and 1" models with Buna-N seals are UL listed

Item Number	Size	Outlet	Seals	Weight (lbs)
110---0200 AF	¾"	Non-threaded	Buna-N	1.25
110---0300 AF	1"	Non-threaded	Buna-N	2.25
110---0600 AF	¾"	Non-threaded	PTFE	1.25
110---1000 AF	¾"	Non-threaded	FKM	1.25
110---1100 AF	1"	Non-threaded	FKM	2.25
110M--0300 AF	1"	Male	Buna-N	2.25



MORRISON BROS. CO.

570 E. 7th Street | Dubuque, IA 52001
 t. 563.583.5701 | 800.553.4840 | f. 563.583.5028
 www.morbros.com