

Model 122 Nozzle Swivel Series

SPECIFICATION SHEET

Application

The 122 series swivel is installed at the nozzle inlet. It is used for ease of operator handling and reduced hose wear. The construction of the swivel provides an unrestricted flow, as well as a smooth swivel rotation. The swivel is rated to 125 PSI and each swivel is tested for electrical continuity per UL 567 prior to being shipped. Each swivel is individually boxed.

Materials of Construction

122ALV

- Aluminum

122BRV

- Brass threaded ends and aluminum center section



Item Number	A	B	C	D	E	Weight
122ALV0100 AS	1"	1"	3.30"	2.25"	F	0.75
122ALV0200 AS	1.25"	1.25"	3.75"	2.25"	F	0.75
122ALV0230 AS	1.5"	1.25"	3.75"	2.25"	F	0.75
122ALV0300 AS	1.5"	1.5"	3.75"	2.25"	F	0.75
122ALV0400 AS	2"	2"	4.06"	2.87"	F	1.0
122BRV0100 AS	1"	1"	3.30"	2.25"	F	1.85
122BRV0200 AS	1.25"	1.25"	3.30"	2.25"	F	1.85
122BRV0230 AS	1.5"	1.25"	3.75"	2.25"	F	1.85
122BRV0300 AS	1.5"	1.5"	3.75"	2.25"	F	1.85

SPECIFICATION OPTIONS:

- A**—Male thread (inches)
- B**—Female thread (inches)
- C**—Overall length (inches)
- D**—Width (inches)
- E**—O-Ring: F=FKM (Rated to minus 40 degrees)
- Weight**—Shipping weight (lbs)