300 Series Manual Nozzles

SPECIFICATION SHEET

Application

Manually-operated shut-off nozzle used for gravity and low pressure fueling and water dispensing.

300AL (¾″)

300ALM

Features and Details

- 35 PSI maximum working pressure
- Heavy duty construction
- **300ALMM** includes arctic mitten expanded handle guard

Materials of Construction

300AL

- Body and cap... Aluminum
- Disc... FKM
- Stem... Aluminum
- O-ring... FKM
- Spout... Aluminum

300ATS

- Body... Aluminum
- Cap... Stainless steel
- Disc... PTFE
- Stem... Stainless steel
- Packing... PTFE
- Spout... Aluminum

300ALM

- Body... Anodized aluminum
- Cap... Anodized aluminum
- Disc... FKM or FDA Buna-N
- Stem... Stainless steel
- O-Ring... Buna-N
- Spout unleaded... Brass ($^{13}/_{16}$″ OD), aluminum ($^{13}/_{16}$″ OD)

Certifications and Listings and Item Numbers on next page.

Certifications and Listings

300ALM

Water nozzles to military drawing #13225E1707 and #13225E9094; Fuel nozzles to CID AA-52030, Type I, Size 1, Class A or B, Style 1

Item Number	Size	Spout	Weight (lbs)
300AL-3100 AN	¾″	13/16″	2.25
300AL-3200 AN	1″	13/16″	2.25
300AL-3300 AN	¾″	15/16″	2.25
300AL-3400 AN	1″	15/16″	2.25
300ATS4000 AN	1″	None	2.30
300ATS4400 AN	1″	15/16″	2.50
300ALM0500 AN	1″	13/16″	2.25
300ALM0600 AM	1″	15/16″	2.25
300ALMM100 AN	1″	15/16″	3.0

**Consult Price List for other options.*

MORRISON BROS. CO.

570 E. 7th Street | Dubuque, IA 52001
t. 563.583.5701 | 800.553.4840 | f. 563.583.5028
www.morbros.com