

Model 560, 561, 562 & 563 Extractors

SPECIFICATION SHEET

Installed on the vent line of an underground storage tank. Allows vent lines to be manifolded and also allows removal of float vent valve (Fig. 317) for repair, replacement, or tank testing. Available with cage or without.

Construction Details

- Cast iron (epoxy coated) body
- Brass cage
- Buna-N o-ring

Certifications & Listings

- CARB 90-09, VR-402 (560, 561, 562 models)
- CARB 95-43, VR-402 (563 models)



562

563

I.D. Number	A	B	C	D	Height	Width	Weight
560---0100 AE	4" X 4" X 2" X 2"	BR	Buna	Y	7.938"	7.594"	18.25
560---0101 MBE	4" X 4" X 2" X 2"	NA	Buna	N	7.938"	7.594"	15.25
561---0100 AE	4" X 4" X 2"	BR	Buna	Y	7.938"	6.531"	15
561---0101 MBE	4" X 4" X 2"	NA	Buna	N	7.938"	6.531"	12
562---0100 AE	4" X 4" X 3" X 2"	BR	Buna	Y	7.594"	7.938"	17.5
562---0101 MBE	4" X 4" X 3" X 2"	NA	Buna	N	7.594"	7.938"	14.5
563---0100 AE	4" X 4" X 3"	BR	Buna	Y	7.938"	6.656"	15.5
563---0101 MBE	4" X 4" X 3"	NA	Buna	N	7.938"	6.656"	12.5

SPECIFICATION OPTIONS:

A—Size
B—Cage material: BR (Brass) or NA
C—O-ring material: Buna
D—Cage: Y (Yes) or N (No)
Height
Width
Weight—Shipping weight (lbs)