Model 560, 561, & 563 Extractors

SPECIFICATION SHEET

Installed on the vent line of an underground storage tank. Allows vent lines to be manifolded and also allows removal of float vent valve (Fig. 317) for repair, replacement, or tank testing. Available with cage or without.

561

563

Construction Details

- Cast iron (epoxy coated) body
- Brass cage
- Buna-N o-ring

Certifications & Listings

- CARB 90-09, VR-402 (560 and 562 models)
- CARB 95-43, VR-402 (563 models)

	I.D. Number	A	B	C	D	Height	Width	Weight
	560---0100 AE	4" X 4" X 2" X 2"	BR	Buna	Y	7.938"	7.594"	18.25
EVR	560---0101 MBE	4" X 4" X 2" X 2"	NA	Buna	N	7.938"	7.594"	15.25
	561---0100 AE	4" X 4" X 2"	BR	Buna	Y	7.938"	6.531"	15
EVR	561---0101 MBE	4" X 4" X 2"	NA	Buna	N	7.938"	6.531"	12
	563---0101 AE	4" X 4" X 3"	BR	Buna	Y	7.938"	6.656"	15.5
EVR	563---0101 MBE	4" X 4" X 3"	NA	Buna	N	7.938"	6.656"	12.5

SPECIFICATION OPTIONS:

A—Size
B—Cage material: BR (Brass) or NA
C—O-ring material: Buna
D—Cage: Y (Yes) or N (No)
Height
Width
Weight—Shipping weight (lbs)

MORRISON BROS. CO.

570 E. 7th Street | Dubuque, IA 52001
t. 563.583.5701 | 800.553.4840 | f. 563.583.5028
www.morbros.com