

### MORRISON BROS. CO.

570 E. 7th Street, P.O. Box 238 | Dubuque, IA 52004-0238 t. 563.583.5701 | 800.553.4840 | f. 563.583.5028 | custserv@morbros.com | www.morbros.com

## MORRISON BROS. CO.

# 715K **Remote Fill Box Series: BACK CONNECTION**



Florida DEP EQ-787

#### Features:

- 10-gallon (37.85 liter) capacity
- 14 gauge steel (powder coated white) or 304 stainless steel
- Pad-lockable
- Integral grounding stud
- Vapor recovery mounting brackets
- Sloped bottom (right to left)
- Drain located in front left corner





<b>External Options</b>	← 715 [	T K 3 - 2 Q B B	- 0 — Internal O
<ul> <li>715TK3</li> <li>10-gallon capacity</li> <li>14-gauge steel (powder coated white)</li> <li>3" back connection</li> <li>On-wall flush mount</li> <li>* four-leg stand not available for this specific model.</li> </ul> 7155-TK3 10-gallon capacity	Model Number	<b>K</b> 3       -       2       Q       B       B	<ul> <li>O</li> <li>Denn</li> <li>O Box only</li> <li>Hand Pump Assembly</li> <li>O No hand pump assembly base package: Steel constr hand pump with PTFE seals and FKM o-rings, reim polyurethane tubing, brass check valve and ball val</li> <li>E E85 Package</li> <li>* Hand Pump Assembly E85 Package: Steel constr hand pump with PTFE seals and FKM o-rings, reim polyurethane tubing, stainless steel check valve and steel constructed hand pump with PTFE seals and o-rings, reinforced polyurethane tubing, stainless steel valve and ball valve.</li> </ul>
<ul> <li>304 stainless steel</li> <li>3" back connection</li> <li>On-wall flush mount</li> </ul> 715TK5 <ul> <li>10-gallon capacity</li> <li>14-gauge steel (powder coated white)</li> <li>3" flanged back connection</li> <li>On-wall flush mount</li> </ul>	0 Box only 2 2" components 3 3" components		<ul> <li>Ball valve</li> <li>Box only</li> <li>Full port NPT ball valve with brass body, hard chrome plated ball &amp; PTFE seals</li> <li>Full port, locking, NPT ball valve with stainless steel body and ball, PTFE seals</li> <li>Inlet Connection</li> <li>Box only</li> <li>Dry disconnect, hardcoated aluminum with stair steel piston, FKM gaskets, and aluminum dust of</li> <li>Dry disconnect, stainless steel body and piston, gasket, and stainless steel dust cap</li> <li>90° quick disconnect aluminum female coupler of</li> </ul>
715–TK3-000B-0         10-gal.         Back connection, fill           715–TK3-2QBB-0         2" - 10-gal.         Back connection, fen           715–TK3-2MBB-0         2" - 10-gal.         Back connection, fen           715–TK3-3QBB-0         3" - 10-gal.         Back connection, fen           715–TK3-3QBB-0         3" - 10-gal.         Back connection, fen           715–TK3-3QBB-0         3" - 10-gal.         Back connection, fen           715–TK3-3DBB-0         3" - 10-gal.         Back connection, fen           715–TK3-3DBB-0         2" - 10-gal.         Back connection, fen           715–TK3-3DBB-0         2" - 10-gal.         Back connection, dry           715S-TK3-2SSS-0         2" - 10-gal.         SS back connection, dry           715S-TK3-2SSS-0         2" - 10-gal.         SS back connection, dry           715S-TK3-3SS0-0         3" - 10-gal.         SS back connection, dry           715S-TK3-3SS0-0         3" - 10-gal.         SS back connection, dry           715S-TK3-3MBB-0         3" - 10-gal.         SS back connection, dry           715S-TK3-3MBB-0         3" - 10-gal.         SS back connection, dry           715S-TK3-3MBB-0         3" - 10-gal.         SS back connection, dry           715S-TK3-3MBD-0         3" - 10-gal.         SS back connection, dry		Weight (lbs)         118.0         122.0         149.0         149.0         161.0         161.0         152.0         114.0         129.0         120.0         120.0	<ul> <li>stainless steel check valve, FKM seals, and alur</li> <li>90° quick disconnect stainless steel coupler with valve, FKM seals, and stainless steel dust plug</li> <li>90° quick disconnect aluminum male adaptor wis stainless steel check valve, FKM seals, and alur dust cap</li> </ul>

### Options



October 2023