SPECIFICATION SHEET

Application

The 73590 cam-and-groove check valves are used in specialized applications where it is necessary and/or convenient to be able to connect and disconnect tank filling components quickly and cleanly.

Materials of Construction

- · Coated aluminum body
- Stainless steel plunger
- FKM discs
- Brass Cam arms (73590CD models only)

Check Valve Adaptors Features and Details

- Male quick connect adaptor mates with traditional quick disconnect fill couplers
- Integrated check valve and fill adaptor reduces product loss at disconnect
- Space saving 90° design fits into small spaces such as Morrison model
 715 remote fill boxes

Item Number	Size	Description	Weight (lbs)
73590CA0200 AV	2"	90° check valve; male adaptor; female threads	2.0
73590CA0300 AV	3"	90° check valve; male adaptor; female threads	5.0

Optional dust caps:

EVR	
06	
EVR	

	Item Number	Size	Description
?	735DCA2000ACEVR	2"	Anodized aluminum dust cap; EVR approved
	735DCA3000ACEVR	3"	Anodized aluminum dust cap; EVR approved

Check Valve Couplers Features and Details

- Female quick disconnect coupler mates with traditional quick connect adaptors
- · Integrated check valve and fill coupler reduces product loss at disconnect
- Space saving 90° design fits into small spaces such as Morrison model 715 remote fill boxes

Item Number	Size	Description	Weight (lbs)
73590CD0200 AV	2"	90° check valve; female coupler, female threads	2.4
73590CD0300 AV	3"	90° check valve; female coupler, female threads	6.0

Optional dust caps:

Item Number	Size	Description			
800DPA0400 1C	2"	Aluminum dust plug			
800DPA0600 1C	3"	Aluminum dust plug			



